

NOTES:

- I. AT PLANTING PRUNE ONLY CROSSING LIMBS, BROKEN OR DEAD BRANCHES, AND, ANY BRANCHES THAT POSE A HAZARD TO PEDESTRIANS PER ANSI STANDARD A300. DO NOT PRUNE INTO OLD WOOD ON EVERGREENS.
- 2. CONTRACTOR SHALL MAXIMIZE EXCAVATED AREA FOR TREE PIT WITHOUT ADVERSELY IMPACTING ADJACENT SITE FEATURES.
- 3. UNLESS OTHERWISE DIRECTED BY THE CITY OF FAIRFAX, BACKFILL SOIL MIXTURE WILL BE 3/4 EXISTING SOIL CLEANED OF DEBRIS (GRAVEL, ROCKS, STICKS, TRASH, ETC.) AND MIXED WITH 1/4 ORGANIC MATERIAL (COMPOSTED BARK, LEAF MOLD, OR OTHER PLANT DEBRIS PROCESSED TO A POINT OF DECAY AND APPROVED BY THE URBAN FORESTER; PEAT MOSS SHALL NOT BE USED).
- 4. CONTRACTOR SHALL LEGALLY REMOVE EXCESS SOIL & DEBRIS FROM THE SITE.
- 5. TREES PLANTED WITHOUT THE TRUNK FLARE VISIBLE WILL BE REJECTED.
- 6. TREES MAY ONLY BE STAKED IF REQUIRED BY THE CITY OF FAIRFAX. REFER TO STAKING DETAILS (L-04 AND L-05).
- 7. ROUGHEN/LOOSEN SIDES OF THE PLANTING HOLE.
- 8. MINIMUM WIDTH OF THE TREE PIT IS THE TWICE THE ROOTBALL DIAMETER OR 5'-0", WHICHEVER IS GREATER.



Department of Public Works 10455 Armstrong Street Fairfax, VA 22030-3630

CITY of FAIRFAX

USE WITH THE FAIRFAX STANDARD SPECIFICATIONS ONLY

www.fairfaxva.gov

STANDARD TREE PLANTING DETAIL

SCALE: NOT TO SCALE	L-01
REVISION DATE:	SHEET #:
JULY 2024	1 of 1